CYPRESS POINT 1.85m MONOWALK WITH ROLLED C & G 54. 54.28 BOULEVARD=1.65m ARC=17.20m SAN INVERT @PL: 51.35 5.50m -2.0% SLOPE 2.0% SLOPE 1.50m 1.50m LOT AREA: 715.07m² **LOT 16** CIVIC ADD. 171) 36.00m 54.58 54.68 36.00m 2.0% SLOPE 2.0% SLOPE - 8.00m 9.00m 3.00m 54.22 54.32 ARC=22.52m -1.50m 2.0% SLOPE \times 54.32 **G** LEGEND **ELEVATION POINT** SERVICE **GARAGE LOCATION** DWELLING >9.0m MIN. SETBACKS DRAINAGE ARROW UTILITY EASEMENT **HYDRANT** ELECTRICAL PROPERTY LINE STREET LIGHT ELECTRICAL PEDESTAL SETBACK FOR GAS LOCATION TRANSFORMER

- NOTES:

 1. THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES SHOWN ARE APPROXIMATE. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK. HE/SHE SHALL BE FULLY RESPONSIBLE FOR ANY DAMAGES WHICH MIGHT BE OCCASIONED BY HIS FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL UNDERGROUND UTILITIES.
- ALL CURB STOPS ARE LOCATED ALONG FRONT PROPERTY LINE. CURB STOP LOCATIONS:

 A) LOTS WITH FRONTAGES 14.0 m OR GREATER SERVICES SHALL BE LOCATED 12.0 m FROM SIDE YARD NEAREST GARAGE
 B) LOTS WITH FRONTAGES LESS THAN 14.0 m SERVICES SHALL BE LOCATED 2.0 m FROM FROM SIDE YARD FURTHEST FROM
- ADD 700.00m TO ALL ELEVATIONS TO OBTAIN GEODETIC

ω

- PROPERTY LINE SETBACKS IN ACCORDANCE WITH ARCHITECTURAL ZONING REQUIREMENTS
- ALL ELEVATIONS BASED ON WSP BENCHMARK #456

Ģ

- FINISHED LOT GRADES SHALL BE IN ACCORDANCE WITH THE CORNER LOT AND MID LOT ELEVATIONS IDENTIFIED
- HOUSE PERIMETER FINISHED GRADE SHALL BE A MINIMUM 0.150m HIGHER THAN ADJACENT SIDEYARD PROPERTY LINE GRADE
- CHANGE WITHOUT NOTIFICATION THIS PLAN IS TO BE USED AS A REFERENCE ONLY AND NOT A LEGAL DOCUMENT. ALL INFORMATION ON THIS PLAN MAY BE SUBLECT TO

Block B, Plan XXX

ZONING: DIRECT CONTROL

